



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

RFID LF/ HF/ UHF Smart Card:

Physical Characteristics

Dimensions 86x54x0.80+/-0.04mm

Material PVC/ PET

User Environment

Operation Temperature -20°C to +55°C (PVC)
-20°C to +150°C (PET)

Performance Specifications

CHIP TK4100, EM4200, T5577, Mifare 1K, Mifare Ultralight, Mifare 4K, Ntag 203, Ultralight-C , I-CODE SLI, Mifare Desfire 2K/4K/8K, Alien H3

Operation Frequency 125KHz/ 13.56MHz / 860~960MHz

Protocol 125KHz/ISO14443A/ ISO15693 / ISO18000-6C

Read Distance 10CM- LF
5CM- HF
8Meters - UHF

Feature Specifications

Feature Printable with offset,silkscreen,personalizing;
Thermal, Injet, Laser print serial number;
Barcode, Signature panel, Magnetic stripe are possible;

Application These Cards are regularly used for Access Control for Office, schools, University, Library, Parking, Monthly Bus Pass/Train Pass ect.

Package

Packing Into Individual Plastic/ Shrink Wrap

200PCS/inner box, 2000PCS/CTN;

13KGS/CTN, carton size: 50x25x14CM



- ❖ 125KHz/ ISO 14443A/ 15693 / ISO18000-6C Compliant
- ❖ Operates at LF 125KHz/ HF 13.56MHz / UHF 860~960MHz
- ❖ Fast read rates for dense reader environments
- ❖ Usage times is above 100,000
- ❖ Rugged & comfortable design
- ❖ Gloss/ Matt surface
- ❖ With Overlay

R

FID Goodwin reserves the right to change its products and services at any time without notice.

Goodwin provides customer assistance in various technical areas, but does not have full access to data concerning the uses and applications of customer's products. Therefore, Goodwin assumes no responsibility for customer product design or for infringement of patents and/or the rights of third parties, which may result from assistance provided by Goodwin