

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

date solid or stranded wire, crimp type terminals or lugs. Multi- placement of these low-profile terminals make them ideally suited for high density packaging. Supplied unassembled or with screw installed and captivated.

PRINCIPAL FEATURES

Stable, no-rock design with exclusive anti-rotational feature Easily mounts with four legs into pre-drilled or punched holes Accepts 14-22 AWG solid or stranded wire, crimp type terminals or lugs

Ideally suited for high-density packaging Easy accessibility for PC board testing

Binding screw is positioned above board level to avoid wicking during wave soldering


HEAD COLOR RED BLACK WHITE BLUE **COLOR SELECTION:** GREEN YELLOW NICKEL



Refer to page 133 for color screws only

Select desired screw terminal and add color suffix to the screw terminal Cat. No.

SNAP-IN PC MOUNT



| M3 THREAD | | M4 THREAD |
|-----------|------------------------------|-----------|
| CAT. NO. | | CAT. NO. |
| 7790 | No Screw Supplied | 7792 |
| 7689* | Screw Supplied Unassembled | 7793 |
| 7695* | Screw Installed & Captivated | 7794 |

*Available with color Coded Screws

SPECIFICATIONS

Rated: 15 Amps

Terminal: .081 (2.05) Brass, Matte Tin Plate

Mounting Detail


Color coded screws available

(add color screw suffix to Cat. No.)

TÓ 5.00

HORIZONTAL TYPE

Screw: Brass, Nickel Plate





PC MOUNT


| M3 THREAD | | M4 THREAD |
|-----------|------------------------------|-----------|
| CAT. NO. | | CAT. NO. |
| 7760 | No Screw Supplied | 7764 |
| 7661* | Screw Supplied Unassembled | 7765 |
| 7662* | Screw Installed & Captivated | 7766 |

*Available with color Coded Screws

VERTICAL TYPE



SNAP-IN PC MOUNT



| M3 THREAD | | M4 THREAD |
|-----------|------------------------------|-----------|
| CAT. NO. | | CAT. NO. |
| 7788 | No Screw Supplied | 7795 |
| 7698* | Screw Supplied Unassembled | 7796 |
| 7696* | Screw Installed & Captivated | 7797 |


*Available with color Coded Screws

SPECIFICATIONS

Rated: 15 Amps

Terminal: .081 (2.05) Brass, Matte Tin Plate

Screw: Brass, Nickel Plate





PC MOUNT

| Mounting Detail | |
|------------------------------|--|
| 7.00 | |
| ±0 9 | |
| 1.85 DIA. HOLE —/ (4) PLS | |

Mounting Dotail

Color coded screws available (add color screw suffix to Cat. No.)

| M3 THREAD | | M4 THREAD |
|-----------|------------------------------|-----------|
| CAT. NO. | | CAT. NO. |
| 7770 | No Screw Supplied | 7767 |
| 7771* | Screw Supplied Unassembled | 7768 |
| 7772* | Screw Installed & Captivated | 7769 |

*Available with color Coded Screws


M5 x 10.00 L.

SCREW

30 AMP - VERTICAL TYPE M4



SNAP-IN PC MOUNT



M4 x 6.00 L. SCREW

SPECIFICATIONS

Rated: 30 Amps


Terminal: .80 Brass, Matte Tin Plate Screw: Brass, Nickel Plate

| CAT. NO. | |
|----------|------------------------------|
| 7798 | No Screw Supplied |
| 7799 | Screw Supplied Unassembled |
| 7800 | Screw Installed & Captivated |

Color coded screws available (add color screw suffix to Cat. No.)

PRINCIPAL FEATURES Compact, heavy duty design

Six snap-in legs for total stability Serrated top surface secures connection



M5

SPECIFICATIONS

Rated: 30 Amps

Terminal: 1.14 Brass, Matte Tin Plate Screw: Brass, Nickel Plate

| CAT. NO. | |
|----------|----------------------------|
| 7807 | No Screw Supplied |
| 7808 | Screw Supplied Unassembled |



SNAP-IN PC MOUNT

Mounting Detail

00 2.57 DIA. HOLE (6) PLS

65

Mounting Detail

-0 0 0

-o o p