



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Technical Datasheet **tasker® C116 - 4x0,14 mm²** Spiral Shielded Cable



A	B	C	D
---	---	---	---

NOTE

CATEGORY

APPLICATIONS

The picture don't represent the real number of conductors.

Spiral Shielded Cable (See Audio Catalogue)

Sound Reproductions and Electronics.

- A:** Soft Black **PVC**.
Outer Cable Diam. Ø 5,20 (±0,10) mm.
- B:** The single conductors are shielded with O.F.C. red copper spiral covering 100%.
- C:** Core Insulation with PVC, colored Black, White, Red, Yellow.
Core Diam. Ø 1,30 (±0,10) mm.
- D:** O.F.C. red copper stranded formation 18x0,10 mm.
Nom. Cross section 4x0,14 mm².

MARKING

CUSTOM

PRODUCTION

tasker® C116 4x0,14 mm² O.F.C. Individually Shielded Cable

This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, or Metallic Armored.

Cable Properties

Conductor Resistance	138 Ω/Km
Capacity Core/Core	150 pF/mt
Capacity Core/Shield	290 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			