

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

FLUKE ®

1577/1587 Insulation Multimeters

New



Fluke 1577



Fluke 1587



Included Accessories

C101 Rugged, utility hard case TL224 SureGrip Silicone Test Lead Set AC285 SureGrip Alligator Clip Set 80BK Integrated DMM Temperature Probe (Type K)

TP165X Remote Test Probe

Ordering Information

Fluke 1577 Insulation Multimeter
Fluke 1587 Insulation Multimeter
Fluke 1587ET Advanced Electrical
Troubleshooting Kit
Fluke 1587MDT Advanced Motor & Drive
Troubleshooting Kit

Two powerful tools in one

The Fluke 1587 and 1577 Insulation Multimeters combine a digital insulation tester with a full-featured True RMS digital multimeter in a single compact, handheld unit, which provides maximum versatility for both troubleshooting and preventive maintenance.

Whether you work on motors, generators, cables, or switch-gear, the Fluke 1587/1577 Insulation Multimeters are ideally suited to help you with your tasks.

Features

| Multimeter Features | 1577 | 1587 |
|--|------|------|
| True RMS Voltage and Current for accurate measurements | • | • |
| Autorange and manual range for easy testing. | • | • |
| Selectable filter for accurate voltage and frequency measurements on motor drives | | • |
| Min Max Recording, Diode test, temperature, capacitance & frequency measurement for maximum flexibility. | | • |
| Insulation features | | |
| User selectable test voltages for many applications | • | • |
| Special remote control probe for easy and safe measurements | • | • |
| Auto-discharge of capacitive voltage for added user protection | • | • |
| Live circuit detection prevents insulation test if voltage $>$ 30V is detected for added user protection | • | • |
| General features | | |
| Auto Power off to save batteries | • | • |
| Large display with backlight | • | • |
| Input Alert to warn for incorrect connections | • | • |
| Continuity | • | • |
| | | |

Insulation Specifications

| | 1577 | 1587 |
|-------------------------|---|---|
| Measurement range | $0.1 \text{M}\Omega$ to $600 \text{M}\Omega$ | $0.01 M\Omega$ to $2G\Omega$ |
| Test voltages | 500V, 1000V | 50V, 100V, 250V, 500V, 1000V |
| Test voltage accuracy | + 20%, - 0% | + 20%, - 0% |
| Insulation test current | 1 mA nominal | 1 mA nominal |
| Auto discharge | Discharge time $<$ 0.5s for C = 1 μ F or less | Discharge time $<$ 0.5s for C = 1 μ F or less |
| Maximum capacitive load | Up to 1µF load | Up to 1µF load |

Multimeter Specifications

| Functions | Maximum | Max. resolution | 1577 | 1587 |
|-------------|-----------------|-----------------|--------------|---------------|
| Voltage DC | 1000V | 1 mV | ± (0.2% + 2) | ± (0.09% + 2) |
| Voltage AC | 1000V | 0.1mV | ± (2% +3) | ± (2% + 3) |
| Current DC | 400mA | 0.01mA | ± (1.0% + 2) | ± (0.2% + 2) |
| Current AC | 400mA | 0.01mA | ± (2% + 2) | ± (1.5% + 2) |
| Resistance | 50.0MΩ | 0.1Ω | ± (1.2% + 2) | ± (0.9% + 2) |
| Capacitance | 9999μF | 1 nF | | ± (1.2% + 2) |
| Frequency | 99.99kHz | 0.01 Hz | | ± (0.1% + 1) |
| Temperature | -40°C to +537°C | 0.1°C | | ± (1% + 10) |

Battery life: Meter: 1000 hrs, Insulation Test: >1000 tests

Size (HxWxD):

203 mm x 100 mm x 50 mm

Weight: 0.55 kg Three Year Warranty

Recommended Accessories











i400

L215