



**EN:** This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at [www.hestore.hu](http://www.hestore.hu).





Figure 1: Internal schematic diagram



### Features

- Low on voltage drop ( $V_{CE(sat)}$ )
- Low  $C_{RES} / C_{IES}$  ratio (no cross-conduction susceptibility)
- Short-circuit withstand time 10  $\mu s$
- IGBT co-packaged with ultrafast free-wheeling diode

### Applications

- High frequency inverters
- Motor drives

### Description

These devices are very fast IGBTs developed using advanced PowerMESH™ technology. This process guarantees an excellent trade-off between switching performance and low on-state behavior.

Table 1: Device summary

| Order code     | Marking    | Package  | Packing       |
|----------------|------------|----------|---------------|
| STGB19NC60KDT4 | GB19NC60KD | D²PAK    | Tape and reel |
| STGF19NC60KD   | GF19NC60KD | TO-220FP | Tube          |
| STGP19NC60KD   | GP19NC60KD | TO-220   |               |

---

**Contents**

|          |                                                                  |           |
|----------|------------------------------------------------------------------|-----------|
| <b>1</b> | <b>Electrical ratings .....</b>                                  | <b>3</b>  |
| <b>2</b> | <b>Electrical characteristics .....</b>                          | <b>4</b>  |
|          | 2.1 Electrical characteristics (curves) .....                    | 7         |
| <b>3</b> | <b>Test circuits .....</b>                                       | <b>10</b> |
| <b>4</b> | <b>Package information .....</b>                                 | <b>11</b> |
|          | 4.1 D <sup>2</sup> PAK (TO-263) type A package information ..... | 11        |
|          | 4.2 D <sup>2</sup> PAK (TO-263) type B package information ..... | 14        |
|          | 4.3 D <sup>2</sup> PAK type A packing information .....          | 17        |
|          | 4.4 D <sup>2</sup> PAK type B packing information .....          | 19        |
|          | 4.5 TO-220FP package information .....                           | 21        |
|          | 4.6 TO-220 type A package information .....                      | 23        |
| <b>5</b> | <b>Revision history .....</b>                                    | <b>25</b> |

# 1 Electrical ratings

Table 2: Absolute maximum ratings

| Symbol                         | Parameter                                                                                                                    | Value                      |          | Unit |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------|----------------------------|----------|------|
|                                |                                                                                                                              | D <sup>2</sup> PAK, TO-220 | TO-220FP |      |
| V <sub>CES</sub>               | Collector-emitter voltage (V <sub>GE</sub> = 0 V)                                                                            | 600                        |          | V    |
| I <sub>C</sub> <sup>(1)</sup>  | Continuous collector current at T <sub>C</sub> = 25 °C                                                                       | 35                         | 16       | A    |
|                                | Continuous collector current at T <sub>C</sub> = 100 °C                                                                      | 20                         | 10       | A    |
| I <sub>CL</sub> <sup>(2)</sup> | Turn-off latching current                                                                                                    | 75                         |          | A    |
| I <sub>CP</sub> <sup>(3)</sup> | Pulsed collector current                                                                                                     | 75                         |          | A    |
| V <sub>GE</sub>                | Gate-emitter voltage                                                                                                         | ±20                        |          | V    |
| I <sub>F</sub>                 | Diode RMS forward current at T <sub>C</sub> = 25 °C                                                                          | 20                         |          | A    |
| I <sub>FSM</sub>               | Surge non repetitive forward current t <sub>p</sub> = 10 ms sinusoidal                                                       | 50                         |          | A    |
| P <sub>TOT</sub>               | Total dissipation at T <sub>C</sub> = 25 °C                                                                                  | 125                        | 32       | W    |
| V <sub>ISO</sub>               | Insulation withstand voltage (RMS) from all three leads to external heat-sink (t = 1 s; T <sub>C</sub> = 25 °C)              |                            | 2500     | V    |
| t <sub>scw</sub>               | Short-circuit withstand time V <sub>CE</sub> = 300 V, T <sub>J</sub> = 125 °C, R <sub>G</sub> = 10 Ω, V <sub>GE</sub> = 12 V | 10                         |          | μs   |
| T <sub>stg</sub>               | Storage temperature range                                                                                                    | - 55 to 150                |          | °C   |
| T <sub>J</sub>                 | Operating junction temperature range                                                                                         |                            |          |      |

**Notes:**

(1) Calculated according to the iterative formula:

$$I_C(T_C) = \frac{T_{J(max)} - T_C}{R_{thj-c} \times V_{CE(sat)(max)}(T_{J(max)}, I_C(T_C))}$$

(2) V<sub>clamp</sub> = 80 % V<sub>CES</sub>, V<sub>GE</sub> = 15 V, R<sub>G</sub> = 10 Ω, T<sub>J</sub> = 150 °C.

(3) Pulse width limited by maximum junction temperature.

Table 3: Thermal data

| Symbol                | Parameter                              | Value                      |          | Unit |
|-----------------------|----------------------------------------|----------------------------|----------|------|
|                       |                                        | D <sup>2</sup> PAK, TO-220 | TO-220FP |      |
| R <sub>thj-case</sub> | Thermal resistance junction-case IGBT  | 1                          | 3.9      | °C/W |
| R <sub>thj-case</sub> | Thermal resistance junction-case diode | 3                          | 5.6      |      |
| R <sub>thj-amb</sub>  | Thermal resistance junction-ambient    | 62.5                       |          |      |

## 2 Electrical characteristics

$T_C = 25\text{ }^{\circ}\text{C}$  unless otherwise specified

Table 4: Static characteristics

| Symbol        | Parameter                            | Test conditions                                                                                         | Min. | Typ. | Max.      | Unit          |
|---------------|--------------------------------------|---------------------------------------------------------------------------------------------------------|------|------|-----------|---------------|
| $V_{(BR)CES}$ | Collector-emitter breakdown voltage  | $I_C = 1\text{ mA}$ , $V_{GE} = 0\text{ V}$                                                             | 600  |      |           | V             |
| $V_{CE(sat)}$ | Collector-emitter saturation voltage | $V_{GE} = 15\text{ V}$ , $I_C = 12\text{ A}$                                                            |      | 2.0  | 2.75      | V             |
|               |                                      | $V_{GE} = 15\text{ V}$ , $I_C = 12\text{ A}$ ,<br>$T_C = 125\text{ }^{\circ}\text{C}$                   |      | 1.65 |           |               |
| $V_{GE(th)}$  | Gate threshold voltage               | $V_{CE} = V_{GE}$ , $I_C = 250\text{ }\mu\text{A}$                                                      | 4.5  |      | 6.5       | V             |
| $I_{CES}$     | Collector cut-off current            | $V_{CE} = 600\text{ V}$ , $V_{GE} = 0\text{ V}$                                                         |      |      | 150       | $\mu\text{A}$ |
|               |                                      | $V_{CE} = 600\text{ V}$ , $V_{GE} = 0\text{ V}$ ,<br>$T_C = 125\text{ }^{\circ}\text{C}$ <sup>(1)</sup> |      |      | 1         | mA            |
| $I_{GES}$     | Gate-emitter leakage current         | $V_{CE} = 0\text{ V}$ , $V_{GE} = \pm 20\text{ V}$                                                      |      |      | $\pm 100$ | nA            |

**Notes:**

<sup>(1)</sup>Defined by design, not subject to production test.

Table 5: Dynamic characteristics

| Symbol    | Parameter                    | Test conditions                                                                                                                                       | Min. | Typ. | Max. | Unit |
|-----------|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|------|
| $C_{ies}$ | Input capacitance            | $V_{CE} = 25\text{ V}$ , $f = 1\text{ MHz}$ ,<br>$V_{GE} = 0\text{ V}$                                                                                | -    | 1170 | -    | pF   |
| $C_{oes}$ | Output capacitance           |                                                                                                                                                       | -    | 127  | -    |      |
| $C_{res}$ | Reverse transfer capacitance |                                                                                                                                                       | -    | 28   | -    |      |
| $Q_g$     | Total gate charge            | $V_{CE} = 480\text{ V}$ , $I_C = 12\text{ A}$ ,<br>$V_{GE} = 0\text{ to }15\text{ V}$<br>(see <a href="#">Figure 20: "Gate charge test circuit"</a> ) | -    | 55   | -    | nC   |
| $Q_{ge}$  | Gate-emitter charge          |                                                                                                                                                       | -    | 11   | -    |      |
| $Q_{gc}$  | Gate-collector charge        |                                                                                                                                                       | -    | 26   | -    |      |

Table 6: Switching on/off (inductive load)

| Symbol         | Parameter             | Test conditions                                                                                                                                                                                                                                                            | Min. | Typ. | Max. | Unit       |
|----------------|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|------------|
| $t_{d(on)}$    | Turn-on delay time    | $V_{CC} = 480\text{ V}$ , $I_C = 12\text{ A}$ ,<br>$R_G = 10\ \Omega$ ,<br>$V_{GE} = 15\text{ V}$<br>(see <a href="#">Figure 19: "Test circuit for inductive load switching"</a> and <a href="#">Figure 21: "Switching waveform"</a> )                                     | -    | 30   | -    | ns         |
| $t_r$          | Current rise time     |                                                                                                                                                                                                                                                                            | -    | 8    | -    | ns         |
| $(di/dt)_{on}$ | Turn-on current slope |                                                                                                                                                                                                                                                                            | -    | 1450 | -    | A/ $\mu$ s |
| $t_{d(on)}$    | Turn-on delay time    | $V_{CC} = 480\text{ V}$ , $I_C = 12\text{ A}$ ,<br>$R_G = 10\ \Omega$ ,<br>$V_{GE} = 15\text{ V}$ , $T_C = 125\text{ }^\circ\text{C}$<br>(see <a href="#">Figure 19: "Test circuit for inductive load switching"</a> and <a href="#">Figure 21: "Switching waveform"</a> ) | -    | 30   | -    | ns         |
| $t_r$          | Current rise time     |                                                                                                                                                                                                                                                                            | -    | 8    | -    | ns         |
| $(di/dt)_{on}$ | Turn-on current slope |                                                                                                                                                                                                                                                                            | -    | 1380 | -    | A/ $\mu$ s |
| $t_{r(Voff)}$  | Off voltage rise time | $V_{CC} = 480\text{ V}$ , $I_C = 12\text{ A}$ ,<br>$R_G = 10\ \Omega$ , $V_{GE} = 15\text{ V}$<br>(see <a href="#">Figure 19: "Test circuit for inductive load switching"</a> and <a href="#">Figure 21: "Switching waveform"</a> )                                        | -    | 35   | -    | ns         |
| $t_{d(off)}$   | Turn-off delay time   |                                                                                                                                                                                                                                                                            | -    | 105  | -    | ns         |
| $t_f$          | Current fall time     |                                                                                                                                                                                                                                                                            | -    | 85   | -    | ns         |
| $t_{r(Voff)}$  | Off voltage rise time | $V_{CC} = 480\text{ V}$ , $I_C = 12\text{ A}$ ,<br>$R_G = 10\ \Omega$ , $V_{GE} = 15\text{ V}$ ,<br>$T_C = 125\text{ }^\circ\text{C}$ (see <a href="#">Figure 19: "Test circuit for inductive load switching"</a> and <a href="#">Figure 21: "Switching waveform"</a> )    | -    | 65   | -    | ns         |
| $t_{d(off)}$   | Turn-off delay time   |                                                                                                                                                                                                                                                                            | -    | 145  | -    | ns         |
| $t_f$          | Current fall time     |                                                                                                                                                                                                                                                                            | -    | 125  | -    | ns         |

Table 7: Switching energy (inductive load)

| Symbol       | Parameter                 | Test conditions                                                                                                                                                                                                        | Min. | Typ. | Max. | Unit    |
|--------------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|---------|
| $E_{on(1)}$  | Turn-on switching energy  | $V_{CC} = 480\text{ V}$ , $I_C = 12\text{ A}$ ,<br>$R_G = 10\ \Omega$ , $V_{GE} = 15\text{ V}$<br>(see <a href="#">Figure 19: "Test circuit for inductive load switching"</a> )                                        | -    | 165  | -    | $\mu$ J |
| $E_{off(2)}$ | Turn-off switching energy |                                                                                                                                                                                                                        | -    | 255  | -    | $\mu$ J |
| $E_{ts}$     | Total switching energy    |                                                                                                                                                                                                                        | -    | 420  | -    | $\mu$ J |
| $E_{on(1)}$  | Turn-on switching energy  | $V_{CC} = 480\text{ V}$ , $I_C = 12\text{ A}$ ,<br>$R_G = 10\ \Omega$ , $V_{GE} = 15\text{ V}$ ,<br>$T_C = 125\text{ }^\circ\text{C}$<br>(see <a href="#">Figure 19: "Test circuit for inductive load switching"</a> ) | -    | 250  | -    | $\mu$ J |
| $E_{off(2)}$ | Turn-off switching energy |                                                                                                                                                                                                                        | -    | 445  | -    | $\mu$ J |
| $E_{ts}$     | Total switching energy    |                                                                                                                                                                                                                        | -    | 695  | -    | $\mu$ J |

**Notes:**

(1) Including the reverse recovery of the diode.

(2) Including the tail of the collector current.

Table 8: Collector-emitter diode

| Symbol    | Parameter                | Test conditions                                                                                                                                                          | Min. | Typ. | Max. | Unit |
|-----------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|------|
| $V_F$     | Forward on-voltage       | $I_F=12\text{ A}$                                                                                                                                                        | -    | 1.9  | -    | V    |
|           |                          | $I_F=12\text{ A}$ , $T_C=125\text{ °C}$                                                                                                                                  | -    | 1.6  | -    | V    |
| $t_{rr}$  | Reverse recovery time    | $I_F=12\text{ A}$ , $V_R=40\text{ V}$ , $di/dt=100\text{ A/}\mu\text{s}$<br>(see <a href="#">Figure 22: "Diode reverse recovery waveform"</a> )                          | -    | 31   | -    | ns   |
| $Q_{rr}$  | Reverse recovery charge  |                                                                                                                                                                          | -    | 30   | -    | nC   |
| $I_{rrm}$ | Reverse recovery current |                                                                                                                                                                          | -    | 2    | -    | A    |
| $t_{rr}$  | Reverse recovery time    | $I_F=12\text{ A}$ , $V_R=40\text{ V}$ , $T_C=125\text{ °C}$ ,<br>$di/dt=100\text{ A/}\mu\text{s}$<br>(see <a href="#">Figure 22: "Diode reverse recovery waveform"</a> ) | -    | 50   | -    | ns   |
| $Q_{rr}$  | Reverse recovery charge  |                                                                                                                                                                          | -    | 70   | -    | nC   |
| $I_{rrm}$ | Reverse recovery current |                                                                                                                                                                          | -    | 4    | -    | A    |

## 2.1 Electrical characteristics (curves)

Figure 2: Output characteristics




Figure 3: Transfer characteristics




Figure 4: Collector-emitter on voltage vs temperature




Figure 5: Gate charge vs gate-source voltage




Figure 6: Capacitance variations




Figure 7: Normalized gate threshold voltage vs temperature




Figure 8: Collector-emitter on voltage vs collector current




Figure 9: Normalized breakdown voltage vs temperature




Figure 10: Switching energy vs temperature




Figure 11: Switching energy vs. gate resistance




Figure 12: Switching energy vs collector current




Figure 13: Turn-off SOA




Figure 14: Emitter-collector diode characteristics




Figure 15: Thermal impedance for TO-220, D<sup>2</sup>PAK




Figure 16: Thermal impedance for TO-220FP




Figure 17: Maximum DC collector current vs T<sub>CASE</sub> for TO-220FP





Figure 18: Maximum power dissipation vs T<sub>CASE</sub> for TO-220FP



AM01504v1

AM01505v1

AM01506v1

AM01507v1

## 4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

### 4.1 D<sup>2</sup>PAK (TO-263) type A package information

Figure 23: D<sup>2</sup>PAK (TO-263) type A package outline





Table 9: D<sup>2</sup>PAK (TO-263) type A package mechanical data

| Dim. | mm    |      |       |
|------|-------|------|-------|
|      | Min.  | Typ. | Max.  |
| A    | 4.40  |      | 4.60  |
| A1   | 0.03  |      | 0.23  |
| b    | 0.70  |      | 0.93  |
| b2   | 1.14  |      | 1.70  |
| c    | 0.45  |      | 0.60  |
| c2   | 1.23  |      | 1.36  |
| D    | 8.95  |      | 9.35  |
| D1   | 7.50  | 7.75 | 8.00  |
| D2   | 1.10  | 1.30 | 1.50  |
| E    | 10.00 |      | 10.40 |
| E1   | 8.50  | 8.70 | 8.90  |
| E2   | 6.85  | 7.05 | 7.25  |
| e    |       | 2.54 |       |
| e1   | 4.88  |      | 5.28  |
| H    | 15.00 |      | 15.85 |
| J1   | 2.49  |      | 2.69  |
| L    | 2.29  |      | 2.79  |
| L1   | 1.27  |      | 1.40  |
| L2   | 1.30  |      | 1.75  |
| R    |       | 0.40 |       |
| V2   | 0°    |      | 8°    |

Figure 24: D<sup>2</sup>PAK (TO-263) type A recommended footprint (dimensions are in mm)





4.2 D<sup>2</sup>PAK (TO-263) type B package informationFigure 25: D<sup>2</sup>PAK (TO-263) type B package outline


Table 10: D<sup>2</sup>PAK (TO-263) type B mechanical data

| Dim. | mm       |      |       |
|------|----------|------|-------|
|      | Min.     | Typ. | Max.  |
| A    | 4.36     |      | 4.56  |
| A1   | 0        |      | 0.25  |
| b    | 0.70     |      | 0.90  |
| b1   | 0.51     |      | 0.89  |
| b2   | 1.17     |      | 1.37  |
| b3   | 1.36     |      | 1.46  |
| c    | 0.38     |      | 0.694 |
| c1   | 0.38     |      | 0.534 |
| c2   | 1.19     |      | 1.34  |
| D    | 8.60     |      | 9.00  |
| D1   | 6.90     |      | 7.50  |
| E    | 10.15    |      | 10.55 |
| E1   | 8.10     |      | 8.70  |
| e    | 2.54 BSC |      |       |
| H    | 15.00    |      | 15.60 |
| L    | 1.90     |      | 2.50  |
| L1   |          |      | 1.65  |
| L2   |          |      | 1.78  |
| L3   |          | 0.25 |       |
| L4   | 4.78     |      | 5.28  |

Figure 26: D<sup>2</sup>PAK (TO-263) type B recommended footprint (dimensions are in mm)

### 4.3 D<sup>2</sup>PAK type A packing information

Figure 27: D<sup>2</sup>PAK type A tape outline



**Figure 28: D<sup>2</sup>PAK type A reel outline**



**Table 11: D<sup>2</sup>PAK type A tape and reel mechanical data**

| Tape |      |      | Reel          |      |      |
|------|------|------|---------------|------|------|
| Dim. | mm   |      | Dim.          | mm   |      |
|      | Min. | Max. |               | Min. | Max. |
| A0   | 10.5 | 10.7 | A             |      | 330  |
| B0   | 15.7 | 15.9 | B             | 1.5  |      |
| D    | 1.5  | 1.6  | C             | 12.8 | 13.2 |
| D1   | 1.59 | 1.61 | D             | 20.2 |      |
| E    | 1.65 | 1.85 | G             | 24.4 | 26.4 |
| F    | 11.4 | 11.6 | N             | 100  |      |
| K0   | 4.8  | 5.0  | T             |      | 30.4 |
| P0   | 3.9  | 4.1  |               |      |      |
| P1   | 11.9 | 12.1 | Base quantity |      | 1000 |
| P2   | 1.9  | 2.1  | Bulk quantity |      | 1000 |
| R    | 50   |      |               |      |      |
| T    | 0.25 | 0.35 |               |      |      |
| W    | 23.7 | 24.3 |               |      |      |

## 4.4 D<sup>2</sup>PAK type B packing information

Figure 29: D<sup>2</sup>PAK type B tape outline




Figure 30: D<sup>2</sup>PAK type B reel outline





Table 12: D<sup>2</sup>PAK type B reel mechanical data

| Dim. | mm   |      |
|------|------|------|
|      | Min. | Max. |
| A    |      | 330  |
| B    | 1.5  |      |
| C    | 12.8 | 13.2 |
| D    | 20.2 |      |
| G    | 24.4 | 26.4 |
| N    | 100  |      |
| T    |      | 30.4 |

## 4.5 TO-220FP package information

Figure 31: TO-220FP package outline



7012510\_Rev\_12\_B

Table 13: TO-220FP package mechanical data

| Dim. | mm   |      |      |
|------|------|------|------|
|      | Min. | Typ. | Max. |
| A    | 4.4  |      | 4.6  |
| B    | 2.5  |      | 2.7  |
| D    | 2.5  |      | 2.75 |
| E    | 0.45 |      | 0.7  |
| F    | 0.75 |      | 1    |
| F1   | 1.15 |      | 1.70 |
| F2   | 1.15 |      | 1.70 |
| G    | 4.95 |      | 5.2  |
| G1   | 2.4  |      | 2.7  |
| H    | 10   |      | 10.4 |
| L2   |      | 16   |      |
| L3   | 28.6 |      | 30.6 |
| L4   | 9.8  |      | 10.6 |
| L5   | 2.9  |      | 3.6  |
| L6   | 15.9 |      | 16.4 |
| L7   | 9    |      | 9.3  |
| Dia  | 3    |      | 3.2  |

## 4.6 TO-220 type A package information

Figure 32: TO-220 type A package outline




Table 14: TO-220 type A package mechanical data

| Dim. | mm    |       |       |
|------|-------|-------|-------|
|      | Min.  | Typ.  | Max.  |
| A    | 4.40  |       | 4.60  |
| b    | 0.61  |       | 0.88  |
| b1   | 1.14  |       | 1.55  |
| c    | 0.48  |       | 0.70  |
| D    | 15.25 |       | 15.75 |
| D1   |       | 1.27  |       |
| E    | 10.00 |       | 10.40 |
| e    | 2.40  |       | 2.70  |
| e1   | 4.95  |       | 5.15  |
| F    | 1.23  |       | 1.32  |
| H1   | 6.20  |       | 6.60  |
| J1   | 2.40  |       | 2.72  |
| L    | 13.00 |       | 14.00 |
| L1   | 3.50  |       | 3.93  |
| L20  |       | 16.40 |       |
| L30  |       | 28.90 |       |
| øP   | 3.75  |       | 3.85  |
| Q    | 2.65  |       | 2.95  |

## 5 Revision history

Table 15: Document revision history

| Date        | Revision | Changes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 08-May-2008 | 1        | Initial release                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 28-May-2008 | 2        | – Value on Table 3: Thermal resistance has been changed.<br>– Inserted Figure 16: Thermal impedance for TO-220, D <sup>2</sup> PAK and<br>Figure 17: Thermal impedance for TO-220FP                                                                                                                                                                                                                                                                                                                                                       |
| 31-Jul-2012 | 3        | Added: Figure 18 and Figure 19 on page 8.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| 17-Jul-2017 | 4        | Modified internal schematic diagram on cover page<br>Modified <a href="#">Table 2: "Absolute maximum ratings"</a> , <a href="#">Table 3: "Thermal data"</a> , and <a href="#">Table 4: "Static characteristics"</a> .<br>Modified <a href="#">Figure 3: "Transfer characteristics"</a> , <a href="#">Figure 4: "Collector-emitter on voltage vs temperature"</a> and <a href="#">Figure 8: "Collector-emitter on voltage vs collector current"</a> .<br>Updated <a href="#">Section 4: "Package information"</a> .<br>Minor text changes. |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2017 STMicroelectronics – All rights reserved

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[STMicroelectronics:](#)

[STGB19NC60KDT4](#) [STGP19NC60KD](#) [STGF19NC60KD](#)