

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.





产品参数表 Product Specification

TH Origin/Elite

Wi-Fi智能开关模块 (温湿度监测)/Smart Temperature and Humidity Monitoring Switch







TH Elite

基本信息 Basic Information

产品系列 DIY 改装件 **Product series** DIY smart switch 产品类型 TH智能开关 Type TH Smart switch

产品型号 THR316, THR320, THR316D, THR320D Model

输入 THR316, THR316D: 100-240V ~ 50/60Hz 16A Max THR320, THR320D: 100-240V ~ 50/60Hz 20A Max Input 输出 THR316, THR316D: 100-240V ~ 50/60Hz 16A Max Output THR320, THR320D: 100-240V ~ 50/60Hz 20A Max

干接点输出 5-30V, 1A Max Dry contact output

MCU ESP32

产品认证 TUV/CE/UKCA/WWA/FCC/RoHS/SRRC Certification

外观信息 Appearance

产品颜色 白色 Color White 产品规格 THR316, THR320: 98x54x27.5mm

THR316D, THR320D: 98x54x31mm **Product size** 包装规格 THR316, THR320: 105x64x35mm THR316D, THR320D: 105x64x39mm Package size

PC V0

THR316D, THR320D: 120g Net weight THR316, THR320: 130g 总重量 Total weight THR316D, THR320D: 150g 外壳材质

Casing material

功能特性 Features

产品净重

加密类型

工作温度

Working height

电源接线线径范围

产品特点 TH Origin/Elite是一款带温湿度检测的智能开关改装件,需连接配套的 温湿度传感器一起使用。 TH Origin/Elite is a DIY smart switch with temperature and humidity

THR316, THR320: 100g

Functions monitoring, and required to use with the temperature and humidity

sensors correspondingly. App 支持平台 Android & iOS

App operating systems

Wi-Fi IEEE 802.11 b/g/n 2.4GHz

无线标准 Wireless Standard

天线 内置FPC天线 FPC board with antenna Antenna

安全机制 WPA/WPA2 Security mode

WEP/TKIP/AES **Encryption type**

室内使用 适用场所 Applicable place Indoor

使用环境 Working Enviroment

-10°C ~ 40°C Working temperature 5%-95% RH, 无冷凝 工作湿度

Working humidity 5%-95% RH, non-condensing 2000米以下 工作海拔

设备安装

安装信息 Installation

防水盒或导轨安装 Installation method Installation of waterproof box or guide rail

接线方式 零线和火线 Wiring way N and L

Less than 2000m

THR320, THR320D: 1.5~6mm² (15~10AWG) Power cord wiring diameter 干接点接线线径范围

THR316D, THR320D: 0.13~0.5mm² (26~20AWG) Dry contact wiring diameter

兼容的传感器设备 Compatible Sensors

温湿度传感器 THS01, Si7021, AM2301

Temperature and humidity sensor 防水温度传感器 DS18B20

MS01

Waterproof temperature sensor 土壤湿度传感器

*使用传感器时,可通过接入传感器延长线(RL560),将传感器放在所需的位置。 * You can connect SONOFF RL560 sensor extension cable to the sensor to monitor the humidity level in an

ideal position.

THR316, THR316D: 1~4mm² (17~11AWG)

Soil moisture sensor