




EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

B...C2300-1500A/B

Silicon-Bridge-Rectifiers Silizium-Brückengleichrichter

Version 2006-07-12



Nominal current Nennstrom	2.3 / 1.5 A
Alternating input voltage Eingangsschwellspannung	40...500 V
Plastic case Kunststoffgehäuse	19 x 3.5 x 10 [mm]
Weight approx. – Gewicht ca.	1.3 g
Plastic material has UL classification 94V-0 Gehäusematerial UL94V-0 klassifiziert	
Standard packaging bulk Standard Lieferform lose im Karton	



Suffix "A" for pinning / für Anschlussfolge [x x x x] = [+ ~ ~ -]
 Suffix "B" for pinning / für Anschlussfolge [x x x x] = [~ + ~ -]



Recognized Product – Underwriters Laboratories Inc.® File E175067
 Anerkanntes Produkt – Underwriters Laboratories Inc.® Nr. E175067

Maximum ratings**Grenzwerte**

Type Typ	Max. alternating input voltage Max. Eingangsschwellspannung V_{VRMS} [V]	Repetitive peak reverse voltage Periodische Spitzensperrenspannung V_{RRM} [V] ¹⁾
B40C2300-1500A/B	40	80
B80C2300-1500A/B	80	160
B125C2300-1500A/B	125	250
B250C2300-1500A/B	250	600
B380C2300-1500A/B	380	800
B500C2300-1500A/B	500	1000

Repetitive peak forward current Periodischer Spitzenstrom	$f > 15 \text{ Hz}$	I_{FRM}	10 A ²⁾
Peak forward surge current, 50/60 Hz half sine-wave Stoßstrom für eine 50/60 Hz Sinus-Halbwellen	$T_A = 25^\circ\text{C}$	I_{FSM}	50/55 A
Rating for fusing, $t < 10 \text{ ms}$ Grenzlastintegral, $t < 10 \text{ ms}$	$T_A = 25^\circ\text{C}$	i^2t	12.5 A ² s
Operating junction temperature – Sperrschichttemperatur		T_j	-50...+150°C
Storage temperature – Lagerungstemperatur		T_s	-50...+150°C

1 Per diode – Pro Diode



2 Valid, if leads are kept to ambient temperature $T_A = 50^\circ\text{C}$ at a distance of 5 mm from case
 Gültig, wenn die Anschlussdrähte in 5 mm vom Gehäuse auf Umgebungstemperatur $T_A = 50^\circ\text{C}$ gehalten werden

Characteristics

Kennwerte

Max. rectified current without cooling fin Dauergrenzstrom ohne Kühlblech	$T_A = 50^\circ\text{C}$	R-load C-load	I_{FAV} I_{FAV}	1.8 A ¹⁾ 1.5 A ¹⁾
Max. rectified current with cooling fin 300 cm ² Dauergrenzstrom mit Kühlblech 300 cm ²	$T_A = 50^\circ\text{C}$	R-load C-load	I_{FAV} I_{FAV}	2.5 A 2.3 A
Leakage current – Sperrstrom	$T_j = 25^\circ\text{C}$	$V_R = V_{RRM}$	I_R	< 10 μA
Thermal resistance junction to ambient air Wärmewiderstand Sperrschicht – umgebende Luft			R_{thA}	< 40 K/W

Type Typ	Max. admissible load capacitor Max. zulässiger Ladekondensator C_L [μF]	Min. required protective resistor Min. erforderl. Schutzwiderstand R_L [Ω]
B40C2300-1500A/B	3100	1.6
B80C2300-1500A/B	1500	3.2
B125C2300-1500A/B	1000	5.0
B250C2300-1500A/B	400	12.0
B380C2300-1500A/B	300	16.0
B500C2300-1500A/B	250	20.0



1 Valid, if leads are kept to ambient temperature $T_A = 50^\circ\text{C}$ at a distance of 5 mm from case
Gültig, wenn die Anschlussdrähte in 5 mm vom Gehäuse auf Umgebungstemperatur $T_A = 50^\circ\text{C}$ gehalten werden