

HESTORE.HU
elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.



24 MHz Rail-to-Rail Amplifiers with Shutdown Option

AD8646/AD8647/AD8648

FEATURES

- Offset voltage: 2.5 mV maximum
- Single-supply operation: 2.7 V to 5.5 V
- Low noise: 8 nV/ $\sqrt{\text{Hz}}$
- Wide bandwidth: 24 MHz
- Slew rate: 11 V/ μs
- Short-circuit output current: 120 mA
- No phase reversal
- Low input bias current: 1 pA
- Low supply current per amplifier: 2 mA maximum
- Unity gain stable

APPLICATIONS

- Battery-powered instruments
- Multipole filters
- ADC front ends
- Sensors
- Barcode scanners
- ASIC input or output amplifiers
- Audio amplifiers
- Photodiode amplifiers
- Datapath/mux/switch control

GENERAL DESCRIPTION

The AD8646 and the AD8647 are the dual, and the AD8648 is the quad, rail-to-rail, input and output, single-supply amplifiers featuring low offset voltage, wide signal bandwidth, low input voltage, and low current noise. The AD8647 also has a low power shutdown function.

The combination of 24 MHz bandwidth, low offset, low noise, and very low input bias current makes these amplifiers useful in a wide variety of applications. Filters, integrators, photodiode amplifiers, and high impedance sensors all benefit from the combination of performance features. AC applications benefit

PIN CONFIGURATIONS




Figure 1. 8-Lead SOIC and MSOP




Figure 2. 10-Lead MSOP




Figure 3. 14-Lead SOIC and TSSOP

from the wide bandwidth and low distortion. The AD8646/AD8647/AD8648 offer high output drive capability, which is excellent for audio line drivers and other low impedance applications.

Applications include portable and low powered instrumentation, audio amplification for portable devices, portable phone headsets, barcode scanners, and multipole filters. The ability to swing rail to rail at both the input and output enables designers to buffer CMOS ADCs, DACs, ASICs, and other wide output swing devices in single-supply systems.

Rev. B

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 www.analog.com
Fax: 781.461.3113 ©2006–2007 Analog Devices, Inc. All rights reserved.

AD8646/AD8647/AD8648

TABLE OF CONTENTS

Features	1	ESD Caution.....	6
Applications.....	1	Typical Performance Characteristics	7
Pin Configurations	1	Theory of Operation	15
General Description	1	Power-Down Operation	15
Revision History	2	Multiplexing Operation.....	15
Specifications.....	3	Outline Dimensions.....	16
Absolute Maximum Ratings.....	6	Ordering Guide	18
Thermal Resistance	6		

REVISION HISTORY

Revision History: AD8646/AD8647/AD8648

10/07—Revision B: Initial Combined Version

Revision History: AD8646

10/07—Rev. 0 to Rev. B

Combined with AD8648.....	Universal
Added AD8647	Universal
Deleted Figure 4 and Figure 7	7
Deleted Figure 33.....	11

8/07—Revision 0: Initial Version

Revision History: AD8648

10/07—Rev. A to Rev. B

Combined with AD8646.....	Universal
Added AD8647	Universal

Deleted Figure 7.....	6
Deleted Figure 11.....	7
Deleted Figure 16 and Figure 17	8
Deleted Figure 24.....	9
Deleted Figure 27, Figure 28, Figure 31, and Figure 32	10

6/07—Rev. 0 to Rev. A

Changes to General Description	1
Updated Outline Dimensions.....	12
Changes to Ordering Guide	12

1/06—Revision 0: Initial Version

SPECIFICATIONS

$V_{SY} = 5 \text{ V}$, $V_{CM} = V_{SY}/2$, $T_A = +25^\circ\text{C}$, unless otherwise noted.

Table 1.

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	V_{OS}	$V_{CM} = 0 \text{ V}$ to 5 V $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	0.6	2.5	3.2	μV
Offset Voltage Drift	$\Delta V_{OS}/\Delta T$	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$	1.8	7.5	7.5	$\mu\text{V}/^\circ\text{C}$
Input Bias Current	I_B	$-40^\circ\text{C} < T_A < +85^\circ\text{C}$ $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	0.3	1	50	pA
Input Offset Current	I_{OS}	$-40^\circ\text{C} < T_A < +85^\circ\text{C}$ $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	0.1	0.5	550	pA
Input Voltage Range	V_{CM}	$-40^\circ\text{C} < T_A < +85^\circ\text{C}$ $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	0	5	250	pA
Common-Mode Rejection Ratio	CMRR	$V_{CM} = 0 \text{ V}$ to 5 V	67	84	84	dB
Large Signal Voltage Gain	A_{VO}	$R_L = 2 \text{ k}\Omega$, $V_O = 0.5 \text{ V}$ to 4.5 V	104	116	116	dB
Input Capacitance						
Differential	C_{DIFF}			2.5	2.5	pF
Common Mode	C_{CM}			6.7	6.7	pF
OUTPUT CHARACTERISTICS						
Output Voltage High	V_{OH}	$I_{OUT} = 1 \text{ mA}$ $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	4.98	4.99	4.99	V
		$I_{OUT} = 10 \text{ mA}$ $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	4.90	4.85	4.92	V
Output Voltage Low	V_{OL}	$I_{OUT} = 1 \text{ mA}$ $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	4.70	8.4	20	mV
		$I_{OUT} = 10 \text{ mA}$ $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	40	78	145	mV
Output Current	I_{SC}	I_{SC} Short circuit	200	200	200	mA
Closed-Loop Output Impedance	Z_{OUT}	At 1 MHz, $A_V = 1$	± 120	5	5	Ω
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	$V_{SY} = 2.7 \text{ V}$ to 5.5 V	63	80	80	dB
Supply Current per Amplifier	I_{SY}	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$	1.5	2.0	2.5	mA
Supply Current Shutdown Mode (AD8647)	I_{SD}	Shutdown of both amplifiers (AD8647 only) $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	10	10	1	nA
						μA
SHUTDOWN INPUTS (AD8647)						
Logic High Voltage (Enabled)	V_{INH}	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$	+2.0	+2.0	+2.0	V
Logic Low Voltage (Power-Down)	V_{INL}	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$			+0.8	V
Logic Input Current (Per Pin)	I_{IN}	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$		1	1	μA
Output Pin Leakage Current		$-40^\circ\text{C} < T_A < +125^\circ\text{C}$ (shutdown active)	1	1	1	nA
DYNAMIC PERFORMANCE						
Slew Rate	SR	$R_L = 2 \text{ k}\Omega$	11	11	11	$\text{V}/\mu\text{s}$
Gain Bandwidth Product	GBP		24	24	24	MHz
Phase Margin	\emptyset_m		74	74	74	Degrees
Settling Time	t_s	To 0.1%	0.5	0.5	0.5	μs
Amplifier Turn-On Time (AD8647)	t_{on}	25°C , $A_V = 1$, $R_L = 1 \text{ k}\Omega$ (see Figure 44)	1	1	1	μs
Amplifier Turn-Off Time (AD8647)	t_{off}	25°C , $A_V = 1$, $R_L = 1 \text{ k}\Omega$ (see Figure 45)	1	1	1	μs

AD8646/AD8647/AD8648

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
NOISE PERFORMANCE						
Peak-to-Peak Noise	e_n p-p	0.1 Hz to 10 Hz		2.3		μV
Voltage Noise Density	e_n	f = 1 kHz		8		nV/ \sqrt{Hz}
		f = 10 kHz		6		nV/ \sqrt{Hz}
Channel Separation	CS	f = 10 kHz		-115		dB
		f = 100 kHz		-110		dB
Total Harmonic Distortion Plus Noise	THD + N	V p-p = 0.1 V, R_L = 600 Ω , f = 25 kHz, T_A = 25°C A_V = +1 A_V = -10		0.010		%
				0.021		%

$V_{SY} = 2.7 \text{ V}$, $V_{CM} = V_{SY}/2$, $T_A = +25^\circ\text{C}$, unless otherwise noted.

Table 2.

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	V_{OS}	$V_{CM} = 0 \text{ V}$ to 2.7 V $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	0.6	2.5	3.2	mV
Offset Voltage Drift	$\Delta V_{OS}/\Delta T$	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$		1.8	7.0	$\mu\text{V}/^\circ\text{C}$
Input Bias Current	I_B	$-40^\circ\text{C} < T_A < +85^\circ\text{C}$ $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	0.2	1	50	pA
					550	pA
Input Offset Current	I_{OS}	$-40^\circ\text{C} < T_A < +85^\circ\text{C}$ $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	0.1	0.5	50	pA
					250	pA
Input Voltage Range	V_{CM}		0	2.7	2.7	V
Common-Mode Rejection Ratio	CMRR	$V_{CM} = 0 \text{ V}$ to 2.7 V	62	79	79	dB
Large Signal Voltage Gain	A_{VO}	$R_L = 2 \text{ k}\Omega$, $V_O = 0.5 \text{ V}$ to 2.2 V	95	102	102	dB
Input Capacitance					2.5	pF
Differential	C_{DIFF}				7.8	pF
Common Mode	C_{CM}					
OUTPUT CHARACTERISTICS						
Output Voltage High	V_{OH}	$I_{OUT} = 1 \text{ mA}$ $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	2.65	2.68	2.68	V
			2.60			V
Output Voltage Low	V_{OL}	$I_{OUT} = 1 \text{ mA}$ $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	11	25	30	mV
						mV
Output Current	I_{OUT}	Short circuit		±63	±63	mA
Closed-Loop Output Impedance	Z_{OUT}	At 1 MHz, $A_V = 1$		5	5	Ω
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	$V_{SY} = 2.7 \text{ V}$ to 5.5 V	63	80	80	dB
Supply Current per Amplifier	I_{SY}	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$		1.6	2.0	mA
					2.5	mA
Supply Current Shutdown Mode (AD8647)	I_{SD}	Shutdown of both amplifiers (AD8647 only) $-40^\circ\text{C} < T_A < +125^\circ\text{C}$	10	10	1	nA
						μA
SHUTDOWN INPUTS (AD8647)						
Logic High Voltage (Enabled)	V_{INH}	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$	+2.0	+2.0	+2.0	V
Logic Low Voltage (Power-Down)	V_{INL}	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$			+0.8	V
Logic Input Current (Per Pin)	V_{IN}	$-40^\circ\text{C} < T_A < +125^\circ\text{C}$			1	μA
Output Pin Leakage Current		$-40^\circ\text{C} < T_A < +125^\circ\text{C}$ (shutdown active)	1	1	1	nA
DYNAMIC PERFORMANCE						
Slew Rate	SR	$R_L = 2 \text{ k}\Omega$		11	11	$\text{V}/\mu\text{s}$
Gain Bandwidth Product	GBP			24	24	MHz
Phase Margin	\emptyset_m			53	53	Degrees
Settling Time	t_s	To 0.1%		0.3	0.3	μs
Amplifier Turn-On Time (AD8647)	t_{on}	25°C , $A_V = 1$, $R_L = 1 \text{ k}\Omega$ (see Figure 41)		1.2	1.2	μs
Amplifier Turn-Off Time (AD8647)	t_{off}	25°C , $A_V = 1$, $R_L = 1 \text{ k}\Omega$ (see Figure 42)		1	1	μs
NOISE PERFORMANCE						
Peak-to-Peak Noise	$e_n \text{ p-p}$	0.1 Hz to 10 Hz		2.3	2.3	μV
Voltage Noise Density	e_n	$f = 1 \text{ kHz}$		8	8	$\text{nV}/\sqrt{\text{Hz}}$
		$f = 10 \text{ kHz}$		6	6	$\text{nV}/\sqrt{\text{Hz}}$
Channel Separation	CS	$f = 10 \text{ kHz}$		-115	-115	dB
		$f = 100 \text{ kHz}$		-110	-110	dB

AD8646/AD8647/AD8648

ABSOLUTE MAXIMUM RATINGS

Table 3.

Parameter	Rating
Supply Voltage	6 V
Input Voltage	GND to V_{SY}
Differential Input Voltage	± 3 V
Output Short Circuit to GND	Indefinite
Storage Temperature Range	-65°C to +150°C
Operating Temperature Range	-40°C to +125°C
Lead Temperature (Soldering 60 sec)	300°C
Junction Temperature	150°C

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

THERMAL RESISTANCE

θ_{JA} is specified for the worst-case conditions, that is, a device soldered in a circuit board for surface-mount packages.

Table 4. Thermal Resistance

Package Type	θ_{JA}	θ_{JC}	Unit
8-Lead SOIC_N	125	43	°C/W
8-Lead MSOP	210	45	°C/W
10-Lead MSOP	200	44	°C/W
14-Lead SOIC_N	120	36	°C/W
14-Lead TSSOP	180	35	°C/W







ESD CAUTION



ESD (electrostatic discharge) sensitive device.

Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

TYPICAL PERFORMANCE CHARACTERISTICS



AD8646/AD8647/AD8648




Figure 10. Output Saturation Voltage vs. Load Current




Figure 13. Output Saturation Voltage vs. Load Current




Figure 11. Output Saturation Voltage vs. Temperature




Figure 14. Output Saturation Voltage vs. Temperature




Figure 12. Input Bias Current vs. Common-Mode Voltage










Figure 15. Input Bias Current vs. Common-Mode Voltage



AD8646/AD8647/AD8648




Figure 22. CMRR vs. Frequency




Figure 25. CMRR vs. Frequency




Figure 23. PSRR vs. Frequency




Figure 26. PSRR vs. Frequency




Figure 24. Overshoot vs. Load Capacitance




Figure 27. Overshoot vs. Load Capacitance




Figure 28. Small-Signal Transient Response




Figure 31. Small-Signal Transient Response




Figure 29. Large-Signal Transient Response




Figure 32. Large-Signal Transient Response




Figure 30. THD + Noise vs. Frequency




Figure 33. THD + Noise vs. Frequency

AD8646/AD8647/AD8648




Figure 34. 0.1 Hz to 10 Hz Voltage Noise




Figure 37. THD + Noise vs. Output Amplitude




Figure 35. Voltage Noise Density vs. Frequency




Figure 38. Input Bias Current vs. Temperature




Figure 36. Supply Current per Amplifier vs. Supply Voltage




Figure 39. Maximum Output Swing vs. Frequency




Figure 40. Supply Current per Amplifier vs. Temperature




Figure 43. Channel Separation




Figure 41. Turn-On Time




Figure 44. Turn-On Time




Figure 42. Turn-Off Time




Figure 45. Turn-Off Time

AD8646/AD8647/AD8648




Figure 46. Supply Current with Op-Amp Shutdown vs. Temperature




Figure 47. Supply Current with Op-Amp Shutdown vs. Temperature

THEORY OF OPERATION

POWER-DOWN OPERATION

The shutdown function of the AD8647 is referenced to the negative supply voltage of the operational amplifier. A logic level high (> 2.0 V) enables the device, while a logic level low (< 0.8 V) disables the device and places the output in a high impedance condition. Several outputs can be wire-ORed, thus eliminating a multiplexer. The logic input is a high impedance CMOS input. If dual or split supplies are used, the logic signals must be properly referred to the negative supply voltage.

MULTIPLEXING OPERATION

Because each op amp has a separate logic input enable pin, the outputs can be connected together if it can be guaranteed that only one op amp is active at any time. By connecting the op amps as shown in Figure 48, a multiplexer can be eliminated. With the reasonably short turn-on and turn-off times, low frequency signal paths can be smoothly selected. The turn-off time is slightly faster than the turn-on time so, even when using sections from two different packages, the overlap is less than 300 nanoseconds.




Figure 48. AD8647 Output Switching





Figure 49. Switching Waveforms

AD8646/AD8647/AD8648

OUTLINE DIMENSIONS




COMPLIANT TO JEDEC STANDARDS MS-012-AA

CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS
(IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR
REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

0124074

Figure 50. 8-Lead Standard Small Outline Package [SOIC_N]
Narrow Body
(R-8)


Dimensions shown in millimeters and (inches)



COMPLIANT TO JEDEC STANDARDS MO-187-AA

Figure 51. 8-Lead Mini Small Outline Package [MSOP]
(RM-8)

Dimensions shown in millimeters




COMPLIANT TO JEDEC STANDARDS MO-187-BA

Figure 52. 10 Lead Mini Small Outline Package [MSOP]

(RM-10)

Dimensions shown in millimeters




COMPLIANT TO JEDEC STANDARDS MO-153-AB-1

Figure 53. 14-Lead Thin Shrink Small Outline Package [TSSOP]

(RU-14)

Dimensions shown in millimeters

AD8646/AD8647/AD8648



COMPLIANT TO JEDEC STANDARDS MS-012-AB
 CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS
 (IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR
 REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

060606-A

Figure 54. 14-Lead Standard Small Outline Package [SOIC_N]
 Narrow Body
 (R-14)
 Dimensions shown in millimeters and (inches)

ORDERING GUIDE

Model	Temperature Range	Package Description	Package Option	Branding
AD8646ARZ ¹	-40°C to +125°C	8-Lead SOIC_N	R-8	
AD8646ARZ-REEL ¹	-40°C to +125°C	8-Lead SOIC_N	R-8	
AD8646ARZ-REEL7 ¹	-40°C to +125°C	8-Lead SOIC_N	R-8	
AD8646ARMZ-R2 ¹	-40°C to +125°C	8-Lead MSOP	RM-8	A1V
AD8646ARMZ-REEL ¹	-40°C to +125°C	8-Lead MSOP	RM-8	A1V
AD8647ARMZ-R2 ¹	-40°C to +125°C	10-Lead MSOP	RM-10	A1W
AD8647ARMZ-REEL ¹	-40°C to +125°C	10-Lead MSOP	RM-10	A1W
AD8648ARZ ¹	-40°C to +125°C	14-Lead SOIC_N	R-14	
AD8648ARZ-REEL ¹	-40°C to +125°C	14-Lead SOIC_N	R-14	
AD8648ARZ-REEL7 ¹	-40°C to +125°C	14-Lead SOIC_N	R-14	
AD8648ARUZ ¹	-40°C to +125°C	14-Lead TSSOP	RU-14	
AD8648ARUZ-REEL ¹	-40°C to +125°C	14-Lead TSSOP	RU-14	

¹ Z = RoHS Compliant Part.

NOTES

AD8646/AD8647/AD8648

NOTES

©2006–2007 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.
D06527-0-10/07(B)



www.analog.com