




EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Data Sheet



Type Number	24276
Designation IEC	LR 44
System	Manganese Dioxide / Zinc / KOH - Electrolyte
Nominal Voltage	1,5 V
Typical Capacity C	155 mAh
Load 5.6 kOhm, at 20°C down to 0.9 V	
Weight (approx.)	2,0 g
Volume	0,51 ccm
Coding.....	Date of Manufacturing Month/Year



Temperature Ranges	min	max.
Storage	-10°C	65°C
Discharge	-10°C	65°C
Dimensions	min	max.
Diameter (Ø)	11,25	11,6
Height (A/B)	5,0	5,4

Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	0.9 V
Continuous 24h/d, 7d/w Current [µA]:	5600 Ω	Time: Capacity [mAh]: Energy [mWh]:	680 h 155 203

* Contact VARTA if the application is intended to be outside the range of -10°C to +65°C.

*Information and contents in this data sheet are for reference purpose only.
They do not constitute any warranty or representation and are subject to change without notice.
For most current information and further details, please contact your VARTA representative.*

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst
Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553
Date of issue: 2014-11-18

Subject to change without prior notice!