

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

| Technical Specifications

Specification		
Pmax	5~800W	±(1.0%+10)
Imp	0~35A	±(1.5%+5)
Vmp	12~60V	±(1.5%+5)
Voc	12~60V	±(1.5%+5)
Isc	0~35A	±(1.5%+5)
Features		
Display	Large LCD (52 x 66mm)	
Reverse polarity connect protection	V	
Over voltage protection	V	
Over current protection	V	
Over temperature protection	V	
Over power protection	V	
Manual MPPT test	V	
Data hold	V	
Power supply	No battery needed powered by solar panel.	
Ovecategory	CAT 0 60V	
Characteristics		
Product color	Red + Black	
Product size	143 x 74 x 25mm	



UNI-TREND TECHNOLOGY















Large LCD with multiple readings





A single measurement that displays all essential test values can significantly enhance work efficiency.

Portable and lightweight design



With its portable and lightweight design, this meter provides operators with convenience and ease of use, making it an incredibly versatile and indispensable tool for a wide range of tasks.

Equipped with MC4 solar panel connector



With the MC4 connector already included, there is no need for additional solar panel connectors. This enables quick and efficient measurements to be performed effortlessly.

MC4 connector wrench



Say goodbye to the frustration of removing MC4 connectors from solar panel output cables! The MC4 Connector Wrench is here to revolutionize your maintenance routine.

Power supply



There is no requirement for batteries as the measurement can be effortlessly performed for extended periods.





