EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

ACR1311U-N2

General

ACR1311U-N2 Bluetooth® NFC Reader combines the latest 13.56 MHz contactless technology with Bluetooth® Smart connectivity for on-the-go smart card and NFC applications.

Feature

◎ USB 2.0 full speed interface
◎ Bluetooth 4.0 smart interface
◎ Plug and Play – CCID support brings utmost mobility
◎ USB Firmware Upgradeability
◎ Smart Card Reader
◎ Application Programming Interface
◎ Supports Android™ 4.3 and above
◎ Supports iOS 5.0 and later
◎ Built-in Peripherals

Technical Specification

Physical characteristics	
Dimensions	60mm(L)×47.98mm(W)×12mm(H)
Weight	20g
Color	White
Bluetooth Interface	
Protocol	Bluetooth Smart (Bluetooth Low Energy /Bluetooth 4.0)
Power Source	Rechargeable Lithium-ion Battery (Charging through USB)
Speed	1Mbps
USB Host Interface	
Protocol	USB Full Speed
Type	Four Line:+5V,GND,D+ and D-
Connector Type	Micro USB
Power Source	From USB Port
Speed	USB Full Speed (12 Mbps)
Cable Length	1 m (Datachable)
Firmware	Upgradeable through USB Interface
Contactless Smart Card Interface	
Standard	ISO 14443 Type A,MIFARE,DESFIRE
Protocol	ISO 14443 T=CL for ISO14443-4 compliant cards, and T+CL Emulation for MIFARE Classic

Shenzhen HCC Technology Co., Ltd.

Address: Rm. 201, 2/F, Bldg. 8, Changyuan New Material Port, No. 2 Gaoxin C. 1st Ave., Yuehai St., Nanshan Dist., Shenzhen, P.R.China
Post Code:518057   Tel:86-755-86655162   Fax:86-755-8606-9640   Web:www.szhcct.com

	1k/4k and NFC tags
Operating Frequency	13.56MHz
Operating Distance	Up to 25mm(depending on tag type)
Smart Card Read/ Write Speed	106Kbps,212Kbps,424Kbps
Antenna Size	28.00mm×32.00mm
Built-in Peripherals	
LED	2bi-color, Red and Blue,Red and Green
Buzzer	Monotone
Operating Conditions	
Temperature	0℃-50℃
Humidity	Max.90%(non-condensing)
MTBF	500,000 hrs
Application Programming Interface	
PC-link Mode	PC/SC CT-API(through wrapper on top of PC/SC)
Certifications/Compliance	EN60950/IEC 60950,ISO 14443,USB Full Speed,Bluetooth Smart, PC/SC,CCID,RoHS 2, REACH, Microsoft® WHQL
Device Driver Operating System Support	Windows®ME,Windows®98,Windows®2000,Windows®XP,Windows®Vista,Windows®7,Windows®8,Windows®8.1,Windows®10,Windows®Server2003,Windows®Sever2008,Windows,®Sever2008R2,Windows®Sever2012,Windows®Sever2012R2,Linux®,Mac OS®, Android, iOS

Picture

Shenzhen HCC Technology Co., Ltd.

Address: Rm. 201, 2/F, Bldg. 8, Changyuan New Material Port, No. 2 Gaoxin C. 1st Ave., Yuehai St., Nanshan Dist., Shenzhen, P.R.China
Post Code:518057   Tel:86-755-86655162   Fax:86-755-8606-9640   Web:www.szhcct.com

Contactless IC Card

Chip:HD S70
(compatible to Mifare 1 S70)

Memory:4K byte
Frequency:13.56MHz

Shenzhen HCC Technology Co., Ltd.

Address: Rm. 201, 2/F, Bldg. 8, Changyuan New Material Port, No. 2 Gaoxin C. 1st Ave., Yuehai St., Nanshan Dist., Shenzhen, P.R.China
Post Code:518057   Tel:86-755-86655162   Fax:86-755-8606-9640   Web:www.szhcct.com