



EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Standard D-Sub PCB Connectors Plugs and Sockets

multicompPRO

**RoHS
Compliant**



Specifications


Electrical Data:

Voltage Rating	: 350V AC
Current Rating	: 5A
Dielectric Withstanding Voltage	: 500V AC (RMS) for 1 minute
Insulation Resistance	: Over 1,000 MΩ minimum
Contact Resistance	: 5mΩ maximum at 1A
Operating Temperature	: -40°C to +100°C

Material:

Insulator	: PBT +30% glass fibre
Pin Contacts	: Brass gold plated
Shell	: Steel, SPCC nickel plated or tin plated

Diagram



Dimensions : Millimetres

Specification Table

Number of Ways	A	B	C ±0.5	D	E	Type	Part Number
9	16.92	24.99	30.81	8.38	12.5	Plug	5502-09PA-01-F1
15	25.25	33.32	39.14			Plug and Socket	5502-15PA-01-F1
25	38.96	47.04	53.04				5502-25PA-01-F1
37	55.42	63.5	69.32				5502-37PA-01-F1
50	52.81	61.11	66.93	11.07	15.37	Plug	5502-50PA-01-F1

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicompPRO