

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.



### **Features**

- Formerly a Riedon<sup>™</sup> product
- Resistances from 0.02 to 260K  $\Omega$
- Resistance tolerances as low as ±0.01 %
- Power rating: 1 to 15 watts
- High power rating in a small package
- Excellent pulse handling
- Operating temp. range: -55 °C to +250 °C
- Low TCR: ±20 PPM/°C standard
- Designed to Mil-R-26 / MIL-R-39007 power ratings
- Non-inductive windings available
- Flame resistant coating
- RoHS compliant\*


### UB Series – Riedon™ Miniature Silicone Coated Power Resistors by Bourns

### **Specifications**

Model and Power	Power Max. Rating Ohms <sup>2</sup>		Dimensions			Designed to Mil-R-26 /
Rating Code	Rating (W)	(Ω)	Α	<b>B</b> <sup>3</sup>	C¹	MIL-R-39007
UB1	1	3.4k	$\frac{6.4 \pm 1.6}{(.250 \pm .062)}$	$\frac{2.2 \pm 0.8}{(.085 \pm .031)}$	$\frac{0.5 \pm 0.05}{(.020 \pm .002)}$	RW-81 RWR-81
UB2	1.5	7.5k	$\frac{7.9 \pm 1.6}{(.312 \pm .062)}$	$\frac{2.0 \pm 0.8}{(.078 \pm .031)}$	$\frac{0.6 \pm 0.05}{(.025 \pm .002)}$	RWR-82
UB3	2	10k	$\frac{10.3 \pm 1.6}{(.406 \pm .062)}$	$\frac{2.4 \pm 0.8}{(.094 \pm .031)}$	$\frac{0.6 \pm 0.05}{(.025 \pm .002)}$	RW-80 RWR-80
UB3C	3	12.5k	$\frac{8.9 \pm 1.6}{(.350 \pm .062)}$	$\frac{4.0 \pm 0.8}{(.156 \pm .031)}$	$\frac{0.8 \pm 0.05}{(.032 \pm .002)}$	_
UB5	4	25k	$\frac{14.2 \pm 1.6}{(.560 \pm .062)}$	$\frac{4.7 \pm 0.8}{(.187 \pm .031)}$		_
UB5C	5	32k	$\frac{12.7 \pm 1.6}{(.500 \pm .062)}$	$\frac{6.4 \pm 0.8}{(.250 \pm .031)}$	$\frac{1.0 \pm 0.05}{(.040 \pm .002)}$	_
UB6	6	50k	$\frac{15.9 \pm 1.6}{(.625 \pm .062)}$	$\frac{6.4 \pm 0.8}{(.250 \pm .031)}$		_
UB10	7	95k	$\frac{22.2 \pm 1.6}{(.875 \pm .062)}$	$\frac{7.9 \pm 0.8}{(.312 \pm .031)}$		RW-84
UB12	10	150k	$\frac{31.0 \pm 1.6}{(1.220 \pm .062)}$	$\frac{7.9 \pm 0.8}{(.312 \pm .031)}$		_
UB15	15	260k	$\frac{45.2 \pm 1.6}{(1.780 \pm .062)}$	$\frac{9.5 \pm 0.8}{(.375 \pm .031)}$		_

#### Notes:

- $^{1}$  Lead Diameter: 18 AWG = 0.040  $^{\prime\prime}$  / 20 AWG = 0.032  $^{\prime\prime}$  / 22 AWG = 0.025  $^{\prime\prime}$  / 24 AWG = 0.020  $^{\prime\prime}$ . Where more than one lead is listed / the **bold** value is standard.
- <sup>2</sup> For non-inductive windings / divide maximum resistance by 2.
- <sup>3</sup> For non-inductive winding where R  $\leq$  0.10 ohms, tolerance is +1.6/-0.0 mm (+0.063/-0.00 ").



Specification	Value		
Tolerances	±0.01 % to ±10 % (1 % Standard)		
Temperature Coefficient	>10 Ω: ±20 PPM/°C 1 Ω to 10 Ω: ±50 PPM/°C <1 Ω: Other TCR values available. Contact Bourns.		
Temperature Range	-55 °C to +250 °C		
Maximum Working Voltage	√ (P * R)		
Dielectric Strength	UB1 / UB2 / UB3: 500 VAC; All Others: 1000 VAC		
Construction	Centerless ground ceramic core Matte tin over copper Flame resistant / High temperature / trivalent / inorganic Silicone coating All welded terminations		

#### **Additional Information**

Click these links for more information:











<u>RUDUCI</u>

CHNICAL INVENTORY
IBRARY

SAMPLES

CONTAC

### How To Order

	UB 5 - 25R F 1				
Model ————————————————————————————————————	re)				
Power Rating Code (See Specification					
Resistance Code For values $\leq 10$ K $\Omega$ , "R" represents decimal point (Example: $25$ R = $25$ $\Omega$ ) For values $> 10$ K $\Omega$ , "K" represents decimal point (Example 1K5 = $1.5$ K $\Omega$ )					
Tolerance $X^{**} = \pm 0.01 \%$ $W^{**} = \pm 0.02 \%$ $V^{**} = \pm 0.025 \%$ $U^{**} = \pm 0.05 \%$ $B = \pm 0.1 \%$ $T = \pm 0.2 \%$ $C = \pm 0.25 \%$	D = ±0.5 % F = ±1 % G = ±2 % H = ±3 % J = ±5 % K = ±10 %				
Internal Use ———					

(Specific TCR values available upon request.)



#### WARNING Cancer and Reproductive Harm www.P65Warnings.ca.gov

\*RoHS Directive 2015/863, Mar 31, 2015 and Annex. Specifications are subject to change without notice. Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at <a href="https://www.bourns.com/docs/legal/disclaimer.pdf">www.bourns.com/docs/legal/disclaimer.pdf</a>.

"Bourns" is a registered trademark of Bourns, Inc. in the United States and other countries. In April 2023, BE Services Company, Inc., a subsidiary of Bourns, Inc., purchased certain assets of Riedon, Inc., including its logo and trademarks and the right to continue to manufacture former Riedon™ products. "Gedon Logo" is a registered trademark of BE Services Company, Inc., in the United States. "Riedon" is a trademark of BE Services Company, Inc.


<sup>\*\*</sup>Contact Bourns for tolerances <±0.01 %.

## **UB Series** – Riedon™ Miniature Silicone Coated Power Resistors by Bourns

## **BOURNS**®

### **Environmental Performance**

Specification (MIL-STD 202)	ΔR		
Dielectric	±0.2 % + 0.05 Ω		
Load Life	To ±1 % depending on size and resistance value		
Storage	±0.2 % + 0.05 Ω		
Moisture Resistance	±0.2 % + 0.05 Ω		
Thermal Shock	±0.2 % + 0.05 Ω		
5X Overload (5 s)	±0.2 % + 0.05 Ω		
Shock	±0.1 % + 0.05 Ω		
Vibration	±0.1 % + 0.05 Ω		



### **Packaging Quantities**

Bourns Model Number	Max. Bulk	10 " Reel	12 "Reel	14 " Reel
UB1	1000	2000		
UB2			0000	5000
UB3			3000	5000
UB3C				
UB5		500	1500	3000
UB5C			1000	1500
UB6		N/A		
UB10			500	1000
UB12				
UB15			N/A	750

# **BOURNS**®

Americas: Tel: +1 951-781-5500 • Email: americus@bourns.com

Mexico: Tel: +52-614-478-0400 • Email: mexicus@bourns.com

Asia: Tel: +886-2-2562-4117 • Email: asiacus@bourns.com

EMEA: Tel: +36 88 885 877 • Email: eurocus@bourns.com

www.bourns.com

## **Legal Disclaimer Notice**



This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: http://www.bourns.com/legal/disclaimers-terms-and-policies

PDF: http://www.bourns.com/docs/Legal/disclaimer.pdf