



**EN:** This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at [www.hestore.hu](http://www.hestore.hu).

HOLDER FOR 3 MODULES, METAL



Figure similar

|                                   |                                    |
|-----------------------------------|------------------------------------|
| product brand name                | SIRIUS ACT                         |
| Product designation               | Commanding and signaling devices   |
| Design of the product             | Holder                             |
| Manufacturer article number       |                                    |
| • of the supplied holder          | <a href="#">3SU1550-0AA10-0AA0</a> |
| Actuator:                         |                                    |
| Design of the operating mechanism | 3-way without module               |
| Number of contact modules         | 0                                  |
| Holder:                           |                                    |
| Material of the holder            | Metal                              |
| Display:                          |                                    |
| Number of LED modules             | 0                                  |
| General technical data:           |                                    |
| Product function                  |                                    |
| • positive opening                | No                                 |
| Product component                 |                                    |
| • diode                           | No                                 |
| • lamp transformer                | No                                 |
| • Light source                    | No                                 |
| • series resistor                 | No                                 |
| Insulation voltage                |                                    |
| • Rated value                     | 500 V                              |
| Degree of pollution               | 3                                  |
| Shock resistance                  |                                    |

|                                                   |                                   |
|---------------------------------------------------|-----------------------------------|
| • acc. to IEC 60068-2-27                          | Sinusoidal half-wave 50 g / 11 ms |
| <b>Vibration resistance</b>                       |                                   |
| • acc. to IEC 60068-2-6                           | 10 ... 500 Hz: 5g                 |
| <b>Surge voltage resistance Rated value</b>       | 6 kV                              |
| <b>Mechanical service life (switching cycles)</b> |                                   |
| • typical                                         | 10                                |
| <b>Equipment marking</b>                          |                                   |
| • acc. to DIN EN 61346-2                          | U                                 |
| • acc. to DIN EN 81346-2                          | U                                 |

#### Auxiliary circuit:

|                              |   |
|------------------------------|---|
| <b>Number of NC contacts</b> |   |
| • for auxiliary contacts     | 0 |
| <b>Number of NO contacts</b> |   |
| • for auxiliary contacts     | 0 |
| <b>Number of CO contacts</b> |   |
| • for auxiliary contacts     | 0 |

#### Connections/ Terminals:

|                          |               |
|--------------------------|---------------|
| <b>Tightening torque</b> |               |
| • for grounding          | 0.8 ... 1 N·m |

#### Ambient conditions:

|                            |                |
|----------------------------|----------------|
| <b>Ambient temperature</b> |                |
| • during operation         | -25 ... +70 °C |
| • during storage           | -40 ... +80 °C |

#### Installation/ mounting/ dimensions:

|                                          |                      |
|------------------------------------------|----------------------|
| <b>Mounting type</b>                     |                      |
| • of modules and accessories             | Front plate mounting |
| <b>Height</b>                            | 40 mm                |
| <b>Width</b>                             | 30 mm                |
| <b>Shape of the installation opening</b> | round                |

#### Certificates/ approvals:

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

##### Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU15500AA100AA0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<https://support.industry.siemens.com/cs/ww/en/ps/3SU15500AA100AA0>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU15500AA100AA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU15500AA100AA0&lang=en)



last modified:



27.04.2015