







EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Modular Einbaubuchsen, 90°, 8-Polig (RJ45), geschirmt Modular Jacks, 90°, 8-poles (RJ45), shielded



Gehäuse

Polyester, glasfaserverstärkt

Kontakte

Phosphorbronze

Kontaktoberfläche

6µ" Gold

Betriebstemperaturbereich

-40°C bis +85°C

Stromnennbelastung

1.5A

Betriebsspannung

125V AC eff.

Housing

Glass filled polyester

Contacts

Phosphorbronze

Contact finish

6µ" gold plating

Operating temperature

-40°C to +85°C




Current rating

1.5A

Voltage rating

125V AC rms

Bestellcode : **A - 2004 - 2 - LP / FS**
Ordercode :



Gehäuse

Polyester, glasfaserverstärkt

Kontakte

Phosphorbronze

Kontaktoberfläche

6µ" Gold

Betriebstemperaturbereich

-40°C bis +85°C

Stromnennbelastung

1.5A

Betriebsspannung

125V AC eff.

Housing

Glass filled polyester

Contacts

Phosphorbronze

Contact finish

6µ" gold plating

Operating temperature



-40°C to +85°C

Current rating

1.5A

Voltage rating

125V AC rms



Bestellcode : **A - 2004 - 2 - LPS**
Ordercode :