



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.



Applications:
Coaxial braided shielded cable for video frequency **MIL. C 17 F Standards.**

Characteristics:
Conductor: stranded in O.F.C. tinned copper
Insulation: Compact PE
Shield: Braided covering **98%** O.F.C. red copper
Sheath: PVC
Sheath colour: **Blue**



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
RG 11 AU	1	1 x 75 Ω (0,88 mm²)	7x0,40	7,3		10,3	100	B	13,5

Conductor Resistance		Capacity Core/shield		Velocity of propagation	
Ω/Km ± 5 %		pF/mt		%	
21		67		66	
Impedance		Voltage		Operative Temperature	
Ω ± 3 %		V		°C	
75		5000		-15 / +70	
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
4,2	6,2	9,3	13,8	20,5	23,4



Applications:
Coaxial braided shielded cable for radio frequency **MIL. C 17 F Standards.**

Characteristics:
Conductor: stranded in CW
Insulation: Compact PE
Shield: Braided covering **98%** O.F.C. tinned copper
Sheath: PVC
Sheath colour: **Blue**



tasker® Code	Cond. number	Cond. number Nominal section	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
RG 174 AU	1	1 x 50 Ω (0,14 mm²)	7x0,16 CW	1,5		2,8	100 500	B B	1,3 6,8

Conductor Resistance		Capacity Core/shield		Velocity of propagation	
$\Omega/\text{Km} \pm 5\%$		pF/mt		%	
290		100		66	
Impedance		Voltage		Operative Temperature	
$\Omega \pm 3\%$		V		$^{\circ}\text{C}$	
50		1500		-15 / +70	
Attenuation db/100mt					
50 MHz	100 MHz	200 MHz	400 MHz	800 MHz	1000 MHz
17,5	25,8	38,2	54,9	77,0	87,5