



HESTORE.HU

elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Specifications	Range	Best Accuracy		
Model		UT15A	UT15B	UT15C
LED AC/DC Voltage Indication (V)	12V	0 ~ 12V	0 ~ 10V	0 ~ 10V
	24V	19V±2V	17V±2V	17V±2V
	50V	48V±6V	35V±6V	35V±5V
	120V	110V±20V	80V±20V	80V±15V
	230V	200V±20V	165V±20V	165V±20V
	400V	340V±30V	300V±30V	300V±30V
	690V	520V±30V	510V±40V	510V±40V
Phase Rotation Test	Operating Voltage: 0V~690V			
	Frequency : 50Hz~ 60Hz	√	√	√
Single Lead(L2)Voltage Detection	Operating Voltage : 100V~690V			
	Frequency: 50Hz~ 400Hz	√	√	√
Continuity Test	Resistance: 0~400KΩ			
	Beeper and LED light Indicator		√	√
Polarity Detection	Positive & Negative	√	√	√
Features				
Water-Proof (IP65)		√	√	√
Auto Range		√	√	√
Work Light		√	√	√
Low Battery Indication	Short circuit two leads,LED and beeper off when the bettery is low	√	√	√
LCD AC/DC Voltage Display	24V~ 690V			±(3%+8)
General Characteristic				
Power	1.5V Batteries (R03) X 2			
LCD Size	UT15C-23 X 12mm			

Product Color	Red and Grey
Product Net Weight	210g
Product Size	275mm X 51mm X 30 mm
Standard Accessories	Batteries