



**EN:** This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at [www.hestore.hu](http://www.hestore.hu).




# BDX33B BDX33C BDX34B BDX34C

## COMPLEMENTARY SILICON POWER DARLINGTON TRANSISTORS


### DESCRIPTION

The BDX33B and BDX33C are silicon Epitaxial-Base NPN power transistors in monolithic Darlington configuration mounted in Jedec TO-220 plastic package. They are intended for use in power linear and switching applications. The complementary PNP types are BDX34B and BDX34C respectively.




TO-220

### INTERNAL SCHEMATIC DIAGRAM



$R_1$  Typ. = 10 K $\Omega$



$R_2$  Typ. = 150  $\Omega$

### ABSOLUTE MAXIMUM RATINGS

| Symbol    | Parameter                                        | NPN | BDX33B     | BDX33C | Unit             |
|-----------|--------------------------------------------------|-----|------------|--------|------------------|
|           |                                                  | PNP | BDX34B     | BDX34C |                  |
| $V_{CBO}$ | Collector-Base Voltage ( $I_E = 0$ )             |     | 80         | 100    | V                |
| $V_{CEO}$ | Collector-Emitter Voltage ( $I_B = 0$ )          |     | 80         | 100    | V                |
| $I_C$     | Collector Current                                |     | 10         |        | A                |
| $I_{CM}$  | Collector Peak Current                           |     | 15         |        | A                |
| $I_B$     | Base Current                                     |     | 0.25       |        | A                |
| $P_{tot}$ | Total Dissipation at $T_c \leq 25^\circ\text{C}$ |     | 70         |        | W                |
| $T_{stg}$ | Storage Temperature                              |     | -65 to 150 |        | $^\circ\text{C}$ |
| $T_j$     | Max. Operating Junction Temperature              |     | 150        |        | $^\circ\text{C}$ |

For PNP types voltage and current values are negative.

## BDX33B BDX33C BDX34B BDX34C

### THERMAL DATA


|                       |                                  |      |      |
|-----------------------|----------------------------------|------|------|
| R <sub>thj-case</sub> | Thermal Resistance Junction-case | 1.78 | °C/W |
|-----------------------|----------------------------------|------|------|

### ELECTRICAL CHARACTERISTICS (T<sub>case</sub> = 25 °C unless otherwise specified)

| Symbol                 | Parameter                                                          | Test Conditions                                                                                                                                                                                                             | Min.      | Typ. | Max.                   | Unit                 |
|------------------------|--------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|------|------------------------|----------------------|
| I <sub>CBO</sub>       | Collector Cut-off Current<br>(I <sub>E</sub> = 0)                  | for <b>BDX33B/34B</b> V <sub>CB</sub> = 80 V<br>for <b>BDX33C/34C</b> V <sub>CB</sub> = 100V<br>T <sub>case</sub> = 100 °C<br>for <b>BDX33B/34B</b> V <sub>CB</sub> = 80 V<br>for <b>BDX33C/34C</b> V <sub>CB</sub> = 100 V |           |      | 0.2<br>0.2<br>5<br>5   | mA<br>mA<br>mA<br>mA |
| I <sub>CEO</sub>       | Collector Cut-off Current<br>(I <sub>B</sub> = 0)                  | for <b>BDX33B/34B</b> V <sub>CE</sub> = 40 V<br>for <b>BDX33C/34C</b> V <sub>CE</sub> = 50V<br>T <sub>case</sub> = 100 °C<br>for <b>BDX33B/34B</b> V <sub>CE</sub> = 40 V<br>for <b>BDX33C/34C</b> V <sub>CE</sub> = 50 V   |           |      | 0.5<br>0.5<br>10<br>10 | mA<br>mA<br>mA<br>mA |
| I <sub>EBO</sub>       | Emitter Cut-off Current<br>(I <sub>C</sub> = 0)                    | V <sub>EB</sub> = 5 V                                                                                                                                                                                                       |           |      | 5                      | mA                   |
| V <sub>CEO(sus)*</sub> | Collector-Emitter Sustaining<br>Voltage (I <sub>B</sub> = 0)       | I <sub>C</sub> = 100 mA for <b>BDX33B/34B</b><br>for <b>BDX33C/34C</b>                                                                                                                                                      | 80<br>100 |      |                        | V<br>V               |
| V <sub>CER(sus)*</sub> | Collector-emitter Sustaining<br>Voltage (R <sub>BE</sub> = 100 Ω)  | I <sub>C</sub> = 100 mA for <b>BDX33B/34B</b><br>for <b>BDX33C/34C</b>                                                                                                                                                      | 80<br>100 |      |                        | V<br>V               |
| V <sub>CEV(sus)*</sub> | Collector-emitter Sustaining<br>Voltage (V <sub>BE</sub> = -1.5 V) | I <sub>C</sub> = 100 mA for <b>BDX33B/34B</b><br>for <b>BDX33C/34C</b>                                                                                                                                                      | 80<br>100 |      |                        | V<br>V               |
| V <sub>CE(sat)*</sub>  | Collector-emitter Saturation<br>Voltage                            | I <sub>C</sub> = 3 A I <sub>B</sub> = 6 mA                                                                                                                                                                                  |           |      | 2.5                    | V                    |
| V <sub>BE*</sub>       | Base-emitter Voltage                                               | I <sub>C</sub> = 3 A V <sub>CE</sub> = 3 V                                                                                                                                                                                  |           |      | 2.5                    | V                    |
| h <sub>FE*</sub>       | DC Current Gain                                                    | I <sub>C</sub> = 3 A V <sub>CE</sub> = 3 V                                                                                                                                                                                  | 750       |      |                        | V                    |
| V <sub>F*</sub>        | Parallel-Diode Forward<br>Voltage                                  | I <sub>F</sub> = 8 A                                                                                                                                                                                                        |           |      | 4                      | V                    |
| h <sub>fe</sub>        | Small Signal Current Gain                                          | I <sub>C</sub> = 1 A V <sub>CE</sub> = 5 V f = 1MHz                                                                                                                                                                         | 100       |      |                        |                      |


\* Pulsed: Pulse duration = 300 μs, duty cycle 1.5 %  
For PNP types voltage and current values are negative.

### Safe Operating Area



## TO-220 MECHANICAL DATA

| DIM. | mm    |      |       | inch  |       |       |
|------|-------|------|-------|-------|-------|-------|
|      | MIN.  | TYP. | MAX.  | MIN.  | TYP.  | MAX.  |
| A    | 4.40  |      | 4.60  | 0.173 |       | 0.181 |
| C    | 1.23  |      | 1.32  | 0.048 |       | 0.051 |
| D    | 2.40  |      | 2.72  | 0.094 |       | 0.107 |
| D1   |       | 1.27 |       |       | 0.050 |       |
| E    | 0.49  |      | 0.70  | 0.019 |       | 0.027 |
| F    | 0.61  |      | 0.88  | 0.024 |       | 0.034 |
| F1   | 1.14  |      | 1.70  | 0.044 |       | 0.067 |
| F2   | 1.14  |      | 1.70  | 0.044 |       | 0.067 |
| G    | 4.95  |      | 5.15  | 0.194 |       | 0.203 |
| G1   | 2.4   |      | 2.7   | 0.094 |       | 0.106 |
| H2   | 10.0  |      | 10.40 | 0.393 |       | 0.409 |
| L2   |       | 16.4 |       |       | 0.645 |       |
| L4   | 13.0  |      | 14.0  | 0.511 |       | 0.551 |
| L5   | 2.65  |      | 2.95  | 0.104 |       | 0.116 |
| L6   | 15.25 |      | 15.75 | 0.600 |       | 0.620 |
| L7   | 6.2   |      | 6.6   | 0.244 |       | 0.260 |
| L9   | 3.5   |      | 3.93  | 0.137 |       | 0.154 |
| DIA. | 3.75  |      | 3.85  | 0.147 |       | 0.151 |



P011C

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a trademark of STMicroelectronics

© 1999 STMicroelectronics – Printed in Italy – All Rights Reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia - Malta - Morocco -  
Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>