



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Microphone cables



Applications:
Unbalanced microphone cable and for sound reproduction.

Characteristics:
Conductor: O.F.C. tinned copper
Cond. Insulation: Compact PE
Core colour: Transparent
Shield: Braided covering 90%
O.F.C. tinned copper
Sheath: PVC
Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C129	1	1 x 0,35 (22 AWG)	11x0,20	3,0	5,2	100	B	3,5

nightly blue®



Applications:
Unbalanced microphone cable and for sound reproduction.

Characteristics:
Conductor: O.F.C. tinned copper
Cond. Insulation: Compact PE
Core colour: Transparent
Shield: Braided covering 100%
O.F.C. tinned copper
Sheath: PVC
Sheath colour: Transparent



tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C195	1	1 x 0,50 (20 AWG)	16x0,20	2,1	6,0	100	B	4,2

nightly blue®



Applications:
Professional unbalanced microphone cable and for sound reproduction.

Characteristics:
Conductor: O.F.C. red copper
Cond. Insulation: PVC
Core colour: White
Inner cotton: Braided covering 95%
Shield: Braided covering 95%
O.F.C. tinned copper
Sheath: PVC
Sheath colours: Red, Blue, Yellow, Green



tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C209	1	1 x 0,75 (18 AWG)	24x0,20	3,0	6,2	100	B	5,3

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
30		236
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70