



EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Triple Output ODP Series

max
378W
power output

3-CH Output with 2-CH 0-30V/6A and 0-6V/3A Programmable DC Power

+ three independent controllable channels

+ max output resolution : 1mV / 1mA

+ low ripples / low noise

+ up to 100 group timers

+ multi- working mode : individual, parallel, and series

+ over-voltage / over-current protection

+ data-logging function: could record the output voltage, and current; and display recorded data in chart

+ 4 inch high resolution (480 x 320 pixels) LCD

+ multi- CI: USB, RS232, and LAN

+ auto-cooling system

+ SCPI, and LabVIEW supported



Model	ODP3033	ODP3063	ODP6033
Channel	3 (independent controllable channel)		
Max Output Power	198W	378W	378W
Output Range	0 - 30V / 3A x 2-CH, 0 - 6V / 3A	0 - 30V / 6A x 2-CH, 0 - 6V / 3A	0 - 60V / 3A x 2-CH, 0 - 6V / 3A

Display	ODP3033	ODP3063	ODP6033
LCD Type	4 inch color LCD		
Display Resolution	480 x 320 pixels, 65536 colors		
Mechanical Specifications	ODP3033	ODP3063	ODP6033
Dimension (W x H x D)	250 x 158 x 358 (mm)		
Device Weight	9.80 kg	12.00 kg	

+ Performance Specifications

The specifications based upon the instrument having run for at least 30 minutes continuously, under the specified operating environment

Model		ODP3033		ODP3063		ODP6033		all 3 models
Channel		CH 1	CH 2	CH 1	CH 2	CH 1	CH 2	CH 3
Output Ratings (0°C - 40°C)	Voltage	0 - 30V		0 - 30V		0 - 60V		6V
	Current	3A		6A		3A		3A
Load Regulation	Voltage	≤0.01% + 3mV						
	Current	≤0.01% + 3mA						
Line Regulation	Voltage	≤0.01% + 3mV						
	Current	≤0.01% + 3mA						

Settings Resolution	Voltage	1mV	
	Current	1mA	
Read Back Resolution	Voltage	1mV	
	Current	1mA	
Settings Accuracy (25°C ± 5°C) (within 12 months)	Voltage	≤0.03% + 10mV	
	Current	≤0.1% + 8mA	≤0.1% + 5mA
Read Back Accuracy (25°C ± 5°C)	Voltage	≤0.03% + 10mV	
	Current	≤0.1% + 8mA	≤0.1% + 5mA
Noise and Ripple (20Hz - 20MHz)	Voltage (Vp-p)	≤2mVp-p	≤3mVp-p
	Voltage (rms)	≤300uVrms	≤1mVrms
	Current (rms)	≤3mA _{rms}	≤4mA _{rms}
Temperature Coefficient (0°C - 40°C)	Voltage	≤0.03% + 10mV	
	Current	≤0.1% + 5mA	
Read Back Temperature Coefficient	Voltage	≤0.03% + 10mV	
	Current	≤0.1% + 5mA	
Parallel Settings Accuracy	Voltage	≤0.02% + 5mV	
	Current	≤0.1% + 30mA	
Programmable Output	Storage	100 groups	
	Time Setting	second	
Data Recording		10 K groups (of voltage, current and power data) recording capacity	
Working Temperature		0 - 40°C	
Communication Interface		USB, RS232, and LAN	

Specifications subject to change without prior notice.

+ Application

R&D laboratory

QC test

industrial automation test


automobile, and electronic circuit test

education / teaching experimentation


+ Accessories The accessories subject to final delivery.



Power Cord



CD ROM




Quick Guide



USB Cable



Fuse



Test Leads
(optional)