





EN: This Datasheet/Document is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.



Rev	AWO #	Description	Date	Appr
-		RELEASED	4/5/05	

APPROVED: _____

DATE: _____ TITLE: _____



PCB LAYOUT



SPECIFICATIONS:

Material:

Insulator: Hi-Temp Thermoplastic, rated UL 94V-0

Insulator color: Black

Contacts: Brass

Plating:

Gold flash over Nickel underplate overall

Electrical:

Operating voltage: 250 VAC max

Current rating: 3 Amps max

Contact resistance: 20 mohms max

Insulation resistance: 5,000 Mohms min @ 500 VDC

Dielectric withstanding voltage: 1,000 VAC for 1 minute

Temperature Rating:

Operating temperature: -40°C to +105°C

Environmental:

Lead free, RoHS compliant

Positions: 02 thru 40
A = .100 [2.54] x No. of Positions
B = .100 [2.54] x No. of Spaces

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED		ADAM TECH 909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710	
INCHES	HOLES	TITLE .100 [2.54] SINGLE ROW PIN HEADER SURFACE MOUNT, TYPE B	
.X ± .10	Ø.X ± .10	SIZE	PART NO.
.XX ± .020	Ø.XX ± .015	X	PH1-XX-UA-SMT-B
.XXX ± .015	Ø.XXX ± .010	REF: S00039T	SCALE: NTS
APPROVALS	DATE	SHEET 1 OF 1	
DRAWN	SS	REV.	
CHECKED			
APPROVED			